

SUSTAINABLE WINDOWS AND DOORS WITH
CHARACTER

Kömmerling 70 double seal

YOUR RESIDENTIAL DOOR: DISTINCT AND SUSTAINABLE

Kömmerling 70 double seal for residential doors

In addition to technical requirements, the design of the residential door also plays an important role, because it is your home's calling card.

The Kömmerling 70 double seal system offers you the option of designing a burglar-proof residential door entirely according to your individual wishes. Inward or outward opening? What kind of door panelling? White or with design lamination? Your taste determines the direction.



Do you expect windows and doors to provide excellent noise protection, reliable protection against forced entry, and state-of-the-art thermal insulation for noticeable savings on your heating costs? So do we. That's why the Kömmerling 70 double seal window and door system offers you just that.

With its minimal construction depth of just 70 mm, it impresses not only with a classic design and a wide variety of versions, but also with top technical values in many areas.

EVERYTHING YOU WANT FROM A WINDOW

Kömmerling 70 double seal

In the window version, for example, the five-chamber technology provides the basis for good thermal insulation, which is clearly noticeable through savings on energy costs. The use of triple glazing or special functional glazing up to 44 mm thick further enhances this effect.

- Offset window design with narrow profile sight lines
- Increased thermal insulation with a U_f value of up to $1.2 \text{ W}/(\text{m}^2\text{K})$
- Wide range of glazing variants: Up to 44 mm thick for the use of triple glazing or special functional glazing
- Greater quality of life thanks to perfect noise protection
- Offers lasting value thanks to robust, high-quality design
- Improved handling ease and reliable functionality through the use of state-of-the-art technology
- Available in PVC white as well as laminated in woodgrains, plain colours and metallic colours



- Outstanding static properties: Four-chamber design with steel reinforcement of maximum dimensions and welded corner connector
- High level of tightness: Double sealing at the threshold with thermal break and threshold connector for an accurate fit between the frame and threshold
- High-quality: Use of special functional glazing or residential door panelling up to 44 mm
- Secure: Excellent burglary protection – depending on the hardware equipment
- Versatile design: Standard PVC white or laminated in woodgrains, plain colours and metallic colours
- Maximum leaf sizes:
Single-leaf residential door: 1100 x 2350 mm
Double-leaf residential door: 1000 x 2350 mm (per leaf)



#KömmerlingForTomorrow

profine GmbH
Kömmerling

Zweibrücker Straße 200
66954 Pirmasens
Germany
Tel. +49 (0) 6331 56 0
E-mail: info@koemmerling.com

www.koemmerling.com

